

Easy programming using selection button sequence

Electronic control and data-recording

Energy management by real time clock

Electronically controlled forced air-cooling

Each column has individual vend motor

24 V D/C motors

Interchangeable parts



## Model

Selections / Columns	10 / 10
Max. product length (mm)	505
Max. product Ø (mm)	72

### Capacities:

Can	0,33 l	680
PET bottle	0,50 l	340

### Dimensions and weights:

H x W x D (mm)	1830 x 1010 x 940
Weight	388 kg

### Performance data:

Refrigeration	0,997 kW
Power supply	230 V / 50 Hz
Max. power consumption	875 W

Control	Executive; MDB
Cabinet	Zinc coated steel, powder painted

### Standard:

Black cabinet  
 5 digit display  
 Safety coin return  
 Anti-Vandalism panel in  
 selection button area  
 Cut out for validator or  
 alternative payment system  
 Lock  
 Choice of neutral front poster

### Options:

Cabinet colour on request  
 Two-line LCD display  
 Security cash system  
 Safety sliding coin insert  
 Anti-rain kit IP 34  
 Loading rack  
 DEX / UCS interface  
 Special coded lock  
 Individual graphics

Vertrieb und Service durch:


**ENGEL**  
 AUTOMATEN+TECHNIK

Asperger Str. 8 D-74321 Bietigheim-Bissingen  
 Tel. 07142 / 9105-0 Fax 07142 / 9105-11  
 Mail: info@engeltec.de www.engeltec.de

SandenVendo GmbH | Spangerstrasse 22 | D-40599 Düsseldorf  
 Fon: +49 (0)211-740 39-0 | Fax: +49 (0)211-748 85 41  
 Web: www.SandenVendo.com | e-Mail: infosvg@sandenvendo.com

